



Overview

The CleanBox Portable Fume Extractor is designed to capture and clean medium to heavy duty welding fumes at source, preventing airborne contaminants from entering your breathing zone.

Featuring an externally articulated capture arm and casters for easy positioning and mobility.

Applications

- Welding
- Grinding
- Soldering
- Sanding

Features

- **Stable:** Low center of mass and four locking casters offers excellent stability during use.
- **High Flow:** Equipped with a 1.5 HP motor, high flow fan impeller, and a large surface area MERV 15 Filter
- **Service Indicator:** Once pressure differential reaches a pre-set value (1,000 kPa) due to a clogged filter, a service indicator light will turn on, to remind the user to inspect and clean or replace the filter.
- **No Special Outlet Required:** 13 Ampere, 120 Volt, single phase power source allows for the Clean Box to be plugged in and used with most outlets.



Dimensions

Model	Net Weight (lbs.)	Capture Arm Length (ft.)	Product Dimensions (<i>without arm</i>)			Cord Length (ft.)
			Width	Height	Length	
CleanBox-10	210	10'	22.5"	31.5"	46"	9'

Technical Specifications

Model	Volumetric Flow Rate (CFM)	Standard Filter	Power	
			Voltage (hz)	Motor (H.P.)
CleanBox-10	1200	Nanofiber MERV 15	110V / 60Hz	1.5



Disclaimer: All data has been collected under specific and controlled conditions. Actual working conditions may cause slight variations to performance to information presented here. Specifications are subject to change without notice.